

# S88 - Portable compressor - 5000 l/min (178 cfm) - 7 bar (100 psi)



- Sullair air-end
- Caterpillar Engine C2.2 DIT
- Direct drive
- Easy maintenance
  
- Waterproof electric connections
- Fewer components
  
- Individual air filtration engine/air-end
- Dual Element air filters engine/air-end

- Engine capable of full load/more than 7 hours operation
- Electronic shutdown System with Annunciation module: engine temperature, engine oil pressure, compressor temperature, underspeed
- Maximum ambient temperature: 46°C (42°C for S88 A model)



**S88 A model, with aftercooler.  
Ideal for sandblasting application.**

BODY	
	S88/S88 A
Fuel tank capacity, liters	75
Air outlet	2 x ¾"
Optionnal air outlet	1"
Total weight, wet (2) kg	840/850
Maximum axle weight (2) kg	860
Total length (2) m	3,10
Total width (2) m	1,45
Height (2) m	1,39

COMPRESSOR	
Delivery (1) m3/min (cfm)	5 (178)
Delivery (1) l/s	83
Rated pressure, bar (psi)	7 (100)
Compressor oil, liters	12

CAT ENGINE (3)	CAT ENGINE C2,2DIT
Number of cylinders	4
Displacement, cm3	2216
Rated speed, tr/min	2300
Rated power, kW (HP)	44,7 (60)

(1) At rated pressure. According to ISO 1217 ±5%  
 (2) Brake with adjustable tow bar. For UK a special straight brake is available. Consult us.  
 (3) Turbo diesel engine